

Crystal Motor Speedway 2021 Pro Stock Rules

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules. NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATIONS OF OR COMPLIANCE WITH THESE RULES AND/OR REGULATIONS. They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator or official.

The race director shall be empowered to permit reasonable and appropriate deviation from any of the specifications herein or impose any further restrictions that in his opinion do not alter the minimum acceptable requirements. NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM SUCH ALTERATION OF SPECIFICATIONS. Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is final.

1. SAFETY EQUIPMENT

Rules apply at all times car is on track. An operational 2-½ pound minimum fire extinguisher with gauge visible for inspection purpose is mandatory in each racecar and tow vehicles. Extinguisher must be mounted in a quick release bracket. DUCT TAPE OR ZIP TIES ARE NOT AN ACCEPTABLE MOUNTING DEVICE.

Rules apply at all times car is on track. Snell-rated SA2010 OR 2015 helmet required. Roll bar padding required in driver compartment. *Recommended: Fire retardant padding.* SFI-approved full fire suit required. Fire retardant gloves, shoes and neck brace (or head and neck restraint) required. Competitors under the age of 18 are recommended to use an SFI 38.1 head and neck restraint system due to the young body and developing bones. Right and left seat head supports required if using head and neck restraint system. *Recommended: Fire retardant head sock and underwear, collapsible steering shaft.* Driver-side window net required, minimum 16 inch by 20-inch ribbon or mesh style and must be mounted to roll cage so latch is at top front of window. Minimum three inch (two inches with head restraint system) wide SFI-approved five-point safety belt assembly required, must be mounted securely to main roll cage. *Recommended: Safety belts no more than two years old.* Any safety equipment physically or visibly worn or damaged must be replaced, regardless of age. All safety equipment must not be altered and must follow manufacturers use, specifications and requirements for installation.

2. APPEARANCE

Door number must be a minimum 4" stroke, with 18" height in CONTRASTING COLOR. Roof number must be a minimum 4" stroke, with 20" height pointed to passenger side of car. **If we can't read your numbers, you will not be scored.** A 6" car number visible from the front and rear of the car is required.


3. BATTERY / STARTER

Battery may be located anywhere outside the driver's compartment. It must arrive at the track fully charged and must be securely mounted and the positive battery post must be insulated. Starters must be in working order. All cars must start under their own power in the staging area or must start on rear of the event. **"NO LITHIUM BATTERIES"**

A clearly labeled Battery ON/OFF 'KILL' switch must be to the right of the driver and within drivers reach. This is for the Safety Crew to be able to kill power to everything.

4. GLASS

Windshield is optional. If used, windshield must be Lexan safety glass, or heavy screen. No Plexiglas. Use of Plexiglas will result in suspension for the night. This is subject to inspection. If no windshield is used a minimum of three windshield bars in front of driver are required. **NO MIRRORS ALLOWED.**



- All roofs must meet all roof dimensions and must be stock appearing.
- No partial roofs, no tilted roofs, no dished-out roofs.
- No wings attached to roof or to side posts.
- Must be a full roof.
- No built-in fiberglass air dams.
- All roof posts must meet outside of car.
- Front roof supports to be 2"x24".
- Side vents on front roof post can extend back no further than 16" bottom, then straight up to roof for an L-configuration. Side vents must meet outside of car.
- Rear roof post supports must meet outside of car on a flat straight line and be stock appearing. Top width between 8" - 12". Bottom width between 18" - 24".
- Rear roof post must be 32" or greater from the rear of trunk.
- Stock appearing rear sail post must be pre-approved, OEM size, and same make and model as nosepiece.
- No Late Model looking noses. Max 2" duckbill.
- Starting in 2021, only nose and fender flairs allowed will be - performance bodies #MD3021-4102 - #PER021-410JK - #PER 33123 L – Dominator nose #Dom-300 - #Dom-330. Performance Bodies Classic dirt nose "Perc11040".
- Maximum nose and fender flare width is 82".
- Noses must be mounted in way that if a square, off of level ground, is touching the nose, at 18" above the ground, the nose must not be any further away, from a level square, than 6". This is to prevent laid back style down force noses.
- Tires must be visible from front of car.
- **Flares or add-ons to nose piece cannot be higher than front fenders.**
- Front bumper and nose must be within 45" from the center of the front wheel and the rear bumper must be within 45" from the center of the rear wheel.
- Front & Rear bumpers not to be wider than body, but must fill area inside panels, tolerance, 2" each side.
- All Pro Stock cars MUST have a rear panel 8" minimum down from deck lid, complete side to side, at 90-degree angle. Must be solid. May have up to a 6" fuel filler door.

- Rear bumper cannot extend more than 8" behind body.
- Bumper heights must be 18" + or - 2" from ground.
- All structural tubing must remain inside body.
- Driver must be able to exit from both sides of car with helmet on.
- Interior of car must be 13 ½" below roll cage minimum and all area of roof, from front window to behind driver's seat. No area of the interior of cockpit can be less than 13 ½" below the roof and roll cage for safety. Easy exiting of car from either side. Windows must have 13 ½" of clearance straight up and down. No support bars blocking right exit from cockpit allowed.

7. ENGINE

Stock American engine. No LS Engines. No cubic inch limit. The forward most spark plug hole may not be set back any further than a perpendicular line with the center of the upper ball joints for each manufacturer. Roller tip and full roller rockers allowed. **No roller camshafts**. Intake must have a 1" minimum inspection hole to view camshaft and lifters. NO ALUMINUM HEADS OR BLOCKS.

8. EXHAUST

Mufflers are MANDATORY. 100-DECIBEL LIMIT. Must be at the end of exhaust, must be unaltered muffler, may be added to your current system. No turndowns. Mufflers must be welded securely in place. Loss of muffler may result in disqualification. Headers are allowed, 1 3/4 " maximum primary tube diameter header. No cross over collector headers allowed. Headers may go over the top of transmission. All 4 exhaust ports from 1 head must be collected within same collector. The 1 3/4" maximum primary tube rule must be maintained until the point where all 4 exhaust ports from one head are collected together. Exhaust may not exit through body panels or door.

9. IGNITION

Distributor must be stock appearing and accept stock distributor cap. No aftermarket dual point ignition or magnetos allowed. No crank fire ignitions. No adjustable ignition control devices. No timing retard controls, or digital gauges (including tach). No electronic monitoring computer devices capable of storing or transmitting information except analog tach. Only stock manufacturer bolt on type parts allowed. Example: MSD or Accel replacement coils or modules allowed providing it fits in stock location. You are allowed ONE Unaltered 12 Volt Ignition System. Ignition must be out of reach of driver and be accessible for tech inspection, all ignition wires must be visible for inspection. One box, One Coil, and One Single Point Distributor. Only Ignition Boxes Allowed Are: MSD 6A p/n 6401, MSD 6ALN p/n 6430, Crane HI-6N Oval track Ignition, p/n 6000-6410, Accel 300+ Ignition w/rev limiter p/n 49300 **and MSD 6CT p/n6427**. MSD E-Curve Distributor is not allowed. HEI distributor is allowed. No electronic traction control devices.

10. CARBURETOR

ONLY 1 Holly #4412--2 bbl (500 not 750) carburetor will be allowed. Absolutely no alterations or modifications to carburetor, except for removal of choke plate. Must have choke horn. Altered carburetors will be CONFISCATED! No transverse mount carburetors allowed. Carburetor must be mounted in conventional manner with float bowl facing forward. Carburetor adapter/spacer allowed, maximum thickness (between carburetor and intake) including gaskets is 1.20 inches.

Top 10 may have to pull carburetor after every feature. Inspection Gauges will be used.

Carburetor may be claimed, following same procedure as shock claim. Claim rule: Carburetor can be claimed for \$250 (\$250 to driver being claimed). See carb and shock claim rules for claiming details.

11. INTAKE

Must have 1-inch minimum inspection hole in intake to view camshaft and lifters or pull distributor to view camshaft and lifters.

No altering intake configuration for an advantage. Only fine tuning will be allowed.

Only the following intakes are allowed:

Weiland: X-Celerator Chevy 7547-1, Ford 7515, 7516, Chrysler 7545

Edelbrock: Torker / Torker II Chevy 5001, 5061, Ford 5021, 5081, 2760, Chrysler 5076

Edelbrock: Performer Chevy 2101, 2116, Ford 2121, 2181, Chrysler 2176
Professional Products: Cyclone Chevy 52001, 52007

Edelbrock: Victor/Victor, Jr. Chevy: 2901, 2912, 2972, 2975; Ford: 2921, 2980, 2981

No welding or modifying of Victor/Victor Jr. will be allowed, exception is 1/2" of port matching will be allowed.

12. FUEL

Gasoline Only. Racing fuel is allowed. No alcohol, no methanol, no E85 / E98. No performance enhancing or scented additives. Fuel must pass both dielectric and chemical tests. **A fuel shut off valve is required on each car. "FUEL SHUT OFF" securely mounted and easily accessible. Track Inspector has the final decision on mounting of shut off valve.**

FUEL SHUT OFF OPTIONS:

If running a ball valve: a fuel shut off valve is required to be within reach of driver and safety crew and to be mounted with the handle through the deck or firewall not be mounted inside the cockpit. The valve and handle must be painted bright orange, and clearly labeled with "FUEL SHUT OFF" securely mounted and easily accessible.

If running an Oberg Valve: An Oberg Fuel Line Safety Valve is required to be installed under body/deck and behind firewalls, in the fuel line and per manufacture instructions; not to be mounted inside the cockpit. The valve must be securely mounted and easily accessible for inspection. Car must be clearly labeled with "Oberg Fuel Valve" composed of a vinyl sticker (1" stroke orange letters with a white 1/2" outline) sticker must contrast from body and graphics to be easily readable. Two stickers will be required; one on the deck where the ball valve would have been mounted and one on the fuel cell or on the trunk lid.

13. FUEL PUMP

Mechanical OEM type push rod fuel pumps only. No electric or belt driven fuel pumps allowed.

14. FUEL CELLS

Fuel cells are mandatory. Tank construction, location and mounting are subject to inspection. A leaking tank is grounds for disqualification. Must have bladder and check valve on fill pipe. Must have canister around tank. If fuel cell does not have aircraft style positive seal filler neck/cap system – a flapper, spring or ball type filler rollover valve is required. Must have approved loop behind the fuel cell, minimum 8" clearance. Gas cap **MUST** be secured to fuel cell by cable, chain or tie strap. **MUST HAVE ROLLOVER VALVE IN VENT TUBE OF FUEL CELL.** Fuel cell must be mounted with minimum 1" square tubing or two solid steel straps around entire cell, 1/8" thick and 2" wide.

15. FIREWALL

The firewall at the front of the cockpit shall be a wall of protection against a fire from the engine compartment. It shall be tightly solid from top to bottom. Not allowing airflow from the engine compartment to the cockpit. Mandatory: 1/8-inch steel or 1/4 inch aluminum plate must be used for drivers' floor.

16. ROLL CAGE

Must be Grand National design with upright supports. Must have halo bar. Four door bars are required in the driver's door. Cage construction should be a minimum of 1 1/2" OD seamless DOM tubing (.095). Front and rear hoop must match main cage pipe size. No aluminum tubing. The driver's seat must be securely fastened at bottom and back of the roll cage, using seat manufacturers' specifications. Drivers head may not extend above roll cage with helmet on. Must have steel plate 18" x 24" x 1/8" in the driver's door, must have steel plate 6" x 12" x 1/8" behind the seat in front of the trailing arms.

17. FRAME

Any 1968 or newer rear wheel drive American made car is permitted in this class. No station wagons or four-wheel drives. All Pro Stocks will have minimum 102" wheelbase, maximum of one-inch difference from right side to left side. All vehicles will be stripped completely of interior, except driver's seat which will be securely fastened to the roll cage and will be equipped with a head rest or a high back racing seat and will be subject to local track

inspection. The front sub and rear clip may be connected with MINIMUM 2"x2" square tubing or minimum 1 3/4" round tubing. All spring and shock mounts must be in stock position. Must have stock front sub-frame or replacement front sub-frame.

ONLY TWO REPLACEMENT FRONT SUB'S ALLOWED. Howe's part #358-8-01, Phone # 989-435-7080. Port City # 100-2-205, Ph # 800-472-2464.

18. STEERING

Aluminum steering quickener allowed. No rack and pinion steering. Quick disconnect steering wheel required. Collapsible Steering Shaft Recommended. No Straight Shafts. Must have minimum ONE knuckle in shaft.

19. FRONT SUSPENSION

NO aluminum suspension pieces (exception is upper A-Arm cross shaft). Rubber, nylon or steel control arm bushings only, no bearing or heim-joint type. Welded single-hole shock mounts only. All coil springs must be over 4 1/2" in diameter. Front springs must be mounted in stock location. No sway bars. Stock type mounted; steel or aluminum cross shaft tubular upper control arms are permitted. Screw jacks are allowed. **NO** coil over springs. No 5th coils. No coil over eliminator. The only lower "A" Arms allowed are: Nova 16", Metric 14.25, Camaro 15.5", and Ford 18".

20. REAR SUSPENSION

NO aluminum suspension pieces. No independent rear suspension. Rubber, nylon or steel control arm bushings only, no offset or bearing type. Single-hole shock mounts only, shocks may be moved, but must remain similar to stock style mounting and location. Rear coil springs must be mounted to rear axle on solid mounts. Springs must be tethered to mount to keep from falling out (Ex: hose clamped or other steel tether). Each rear coil spring may be mounted in front, on top or behind the axle tube as long as the measurement from the centerline of each spring and the centerline of the axle is between zero inches and five and half inches (5 1/2"). Steel coil over eliminators allowed on rear suspension only. Spring location measurements still apply. Bottom control arm mounts on rear end must match side to side. Bottom trailing arm can be no longer than 28" center of mounting bolt to center of mounting bolt and must measure within 2" right to left.

All coil springs must be over 4 1/2" in diameter. Screw jacks are allowed. All heim joints must be steel, 3/4" (minimum). **NO** coil over springs. **NO** torque arms or torque links. Steel or composite rear leaf spring allowed. No 5th coils. No swing arm suspension. All brackets must be welded on rear end. Only 3 type of rear suspension allowed, traditional 3 Link (2 trailing arms, 1 pan hard bar, 1 pull bar), traditional Leaf spring rear suspension and stock 4 link suspension.

21. CLUTCH

No (in and out) boxes, all gears must be clutch operated (with motor running and car in still position, driver must be able to engage car in gear and move forward and backward at time of inspection).

22. TRANSMISSION

Any transmission, manual or automatic. **NO** quick-change transmissions. Must have scatter shield or protective plate 180 degrees around clutch. If L-plate is used, 1/8" steel plate is minimum thickness that will be allowed. Bert or Brinn type transmissions will be allowed, no ball spline. Drive Train must be disengage-able. **NO** direct drive systems.

23. DRIVE SHAFT

Magnetic Steel drive shaft only, must be painted white and have a steel drive shaft loop measuring 1/4" thick by 2 inches wide, located on the forward 1/3 to prevent it from dropping onto the track.

24. REAR AXLE

Any steel approved OEM passenger car or truck non-cambered rear end (housing and carrier) allowed. Safety hubs (floater) allowed. All components must be steel, exceptions are: lowering blocks, axle cap, and drive flange may be aluminum. One-inch inspection hole in housing required. Full steel spool, steel mini spool or welded rear end only. Steel axles only. No quick-change devices. One-piece drive flange only. No torque-dividing differentials. No Gold Tracks. No Lockers. No scalloped ring gears. Quick change rear end allowed with steel tubes.

25. BRAKES

Stock four wheel hydraulic brakes. All must be in working condition. Neal type brake pedal assembly permitted. Single piston, steel calipers only. Brake caliper must be unaltered. No shut off valves. No ratchet valves. No Left to Right proportioning allowed. One Front to Rear proportioning device (brake adjuster) allowed. No pinched off brake lines. All Brake lines must be visible. **NO SOLID ROTORS MUST BE VENTED AS CAST.**

26. HUBS & WHEELS

Eight (8) inch maximum, racing wheels and 1 inch racing / safety lug nuts required for all wheels. **NO Wide 5s** allowed. Bead Lock Wheel allowed on Right Rear Only, if running bead lock, right rear tire must have at least 17 pounds of air after race. Magnetic steel wheels only, no plastic or carbon fiber wheels allowed. Maximum overall width shall not exceed 80 inches from outside of tire-to-outside of tire. Aluminum spacers only. **NO SOLID ROTORS MUST BE VENTED AS CAST**

27. SHOCKS

One shock absorber allowed per wheel. No air coil-over or struts allowed on the front. No Schrader or Bladder type valve allowed. Steel racing shocks are allowed on the front and rear. One 90/10 shock allowed, mounted from top of rear end housing to roll cage. No external adjustable shocks. No bump stops.
NO BULB SHOCKS NO BUMP STOPS INTERNAL OR EXTERNAL. UN TAMPERED

28. SHOCK CLAIM

\$50.00 per shock, may claim any or all shocks. See claim rules.

29. TIRES

American Racer P245/70D-15 tires only. Tire must have MSPA stamp. No Hoosiers, no McCreary. You may groove, sipe and/or grind tires. Chemical alterations, vulcanizing, tire softening, defacing and/or altering the face of the tire lettering and/or tire stamping will not be permitted. Chemicals or tire softening is not permitted at any time. Tires will be subject to a durometer test. Your tires must be harder than the baseline determined by CMS officials. Tires may be inspected at any time. Tire pressure must be at least 17 lbs on right rear if running bead lock wheel, after each race.

30. RADIOS

No radios, **EXCEPT MANDATORY RACECEIVERS**, allowed in car, or with any pit member or anyone connected with the racecar.

31. WEIGHT

2,800 lbs minimum. Added weight **MUST** be in plain sight, painted white or silver, **MUST** have the car number painted on it in a contrasting color and must be readable. No cement pellet or liquid style weights. Weights must be securely mounted to the car with the minimum of two (2) ½" bolts and nuts per 50 pounds of weight. Loss of any weights may be grounds for disqualification. No weight on rear bumper or outside body of the car. No weight added to rear end housing.

32. WRECKER HOOKS

MANDATORY – FRONT AND REAR. CHAINS MUST BE USED. Cables are not acceptable tow hooks. Tow hook cannot extend in front of car. Both must be easily accessible. If there are no wrecker hooks on the car, it will be pushed, towed, or dragged to the infield until after the racing program is completed.

NEITHER WRECKER CREWS NOR RACETRACK PERSONNEL WILL BE RESPONSIBLE FOR ANY DAMAGE DONE TO THE ANY VEHICLE.

CARBURETOR AND SHOCK CLAIM PROCEDURE

1. For the first two weeks, you must have finished in the top 20 in points from the previous year to claim. Driver must have raced the first night in order to claim on the second night. Thereafter, you must have raced the previous two points nights in order to claim.

2. Driver only allowed one claim per event, regardless of outcome. No driver can claim the same driver's shocks more than one, or carburetor more than once per calendar year. Driver being claimed is subject to only one claim per event. If multiple claims are made on same driver, shock claim takes precedence over carb claim. If there are multiple claims over the same piece, a coin flip will take place.
3. Top four finishers are to report directly to the claim area and may be claimed by any driver finishing fifth on back in feature who is scored on the lead lap. If one of the top four drivers are disqualified, fifth place driver is not eligible to be claimed.
4. Failure to report directly to claim area will result in disqualification and loss of points and pay for first infraction. Second infraction will be treated as a claim refusal.
5. Driver making claim must have legal car, must drive directly to claim area, and have correct amount of cash. Claim must be made to official immediately after finish of feature. Claiming driver is to remain in the car and have no communication with another driver or crew member until the official is notified.
6. Only driver may claim, and only driver may agree to sell or refuse. Claim is not charged to drivers not awarded claimed item.
7. Should any driver voluntarily withdraw a legal cash claim, they will be charged with the claim and fined \$200.00.
8. All claimed items will be removed at the track in a reasonable amount of time, at discretion of official.
9. Any sabotage to claimed items will result in same penalties as a claim refusal. Claim will be disallowed, and money returned to claimer, with no claim charged to claimer.
10. Claiming driver must be in a legal car. If claimed car is deemed illegal, claim will proceed, and any penalty will be assessed after item is removed and transferred.
11. Any unsportsmanlike conduct during the claim procedure will result in a \$100.00 fine and/or suspension.
12. Promoter may claim any claimable item at any time, unless that driver has made a legal claim in that event.
13. During any claim, item should be inspected for legality. If item is found to be illegal, driver will be disqualified. Claimer then has the option to accept or decline the claim. If declined, the claimer will not be charged with the claim.
14. Refusal to sell will forfeit all cash and contingency winnings for feature, any trophy earned, and ALL-season points. Driver will be suspended for 30 days from any MSPA track and will have to pay \$250.00 fine before racing in the Pro Stock class again and cannot make a claim at CMS for one calendar year. Any driver found to be claiming for anyone other than him/herself will lose all points for the season and will be suspended for 30 calendar days.
15. Driver may only make one carburetor claim and one shock claim per season, unless that driver has had 2 claims against them. Then that driver may make one additional claim.